

- Features

1. Various high power inductors are superior to be high saturation for surface mounting.

• 特點

- 特點
1. 廣闊的感值範圍，是高飽和表面貼裝的最佳選擇。



• Applications

1. Power supply for VTR、OA equipment.
 2. LCD television set、notebook PC.
 3. Portable communication, equipments.
 4. DC/DC converters, etc.

應用

- 1. 錄影機、辦公自動設備.
 - 2. 液晶電視機、筆記型電腦.
 - 3. 通訊設備.
 - 4. 直流對直流電源供應器等.

ELECTRICAL CHARACTERISTICS FOR BCEP125U SERIES



- (1). Inductance tested at 0.25V. Tolerance of inductance: $\pm 20\%$ (M).
 - (2). DCR test temp. limits 25°C .
 - (3). This indicates the value of current when the inductance is 25% lower than its initial value at D.C. superposition or D.C. current.
 - (4). To load current onto the components under normal ambience, which cause the temp. change as $\Delta t=40^{\circ}\text{C}$ or more lower current.
 - (5). Please refer saturated current or the minimum temperature current as standard.

- (1).電感測試條件為 0.25V。電感的公差為: $\pm 20\%$ (M).
 - (2).電阻 (測試) 溫度為 25°C。
 - (3).是在疊加直流或者直流負載的狀況下，電感比其初始值下降 25%時的電流。
 - (4).在空氣中，一元器件通以電流，使元件表面溫度變化為 $\Delta t=40^\circ\text{C}$ 或低一些的電流值。
 - (5).使用時，請參照飽和電流、溫升電流最小的電流為額定電流。